



DX11S COMMERCIAL

SPLIT SYSTEM AIR CONDITIONERS
7½ & 10 TONS

SUBMITTAL DATA FORM

Job Name _____

Location _____

Purchaser _____

Order No. _____

Engineer _____

Unit No. _____

Model No. _____

Unit Designation _____

Performance Data Certified By: _____



Standard Features

- R-410A chlorine-free refrigerant
- Energy-efficient compressor
- Factory-installed filter dryer
- Copper tube/enhanced aluminum fin coil
- Service valves with sweat connections and easy-access gauge ports
- Contactor with lug connection
- Ground lug connection
- ARI Certified; ETL Listed

Cabinet Features

- Innovative sound control top design
- Steel louver coil guard
- Heavy-gauge galvanized-steel cabinet
- Attractive Nickel Gray powder-paint finish with 500-hour salt-spray approval
- Top and side maintenance access
- Single-panel access to controls with space provided for field-installed accessories
- When properly anchored, meets the 2001 Florida Building Code unit integrity requirements for hurricane-type winds (Anchor bracket kits available.)



* Complete warranty details available from your local dealer or at www.daikincomfort.com.

PERFORMANCE DATA FOR SPLIT SYSTEM

OUTDOOR UNIT: _____

Cooling Performance

Total Capacity _____ MBH

Sensible Capacity _____ MBH

Outdoor Design TMP _____ °F DB / WB

Air Temp entering _____

Evaporator Coil _____ °F

Power Input Required _____ kW
(less blower motor)

INDOOR UNIT: _____

Heating Performance

Total Heating Capacity _____ kW
_____ BTU/h

Supply Air Blower Performance

Total Supply Air _____ CFM

Ext. Static Pressure _____ IWG

Blower Speed _____ RPM

Power Output Required _____ BHP

Motor Ratings _____ HP

Power Input Required _____ kW

Electrical Data

Power Supply _____

Total Unit Amps _____

Max Overcurrent Device:

Fuse _____ Breaker _____ Amps _____

NOTES

CERTIFIED DIMENSIONS

ECON.	REV.	ZONE	DESCRIPTION	CHK	DR.	DATE
XXXXXX	A	XXXXX	INITIAL RELEASE	-	XXX	XXXX-XX

MODEL	DIMENSIONS		
	W"	D"	H"
DX11S0903A	35½	35½	41½
DX11S0904A	35½	35½	41½
DX11S1203A	35½	35½	41½
DX11S1204A	35½	35½	41½

Top View

Side View

Rear View

THE GOODMAN MANUFACTURING COMPANY, L.P.

MODEL: **DX11S**

DATE: BY: CHECKED BY: DATE:

DESIGNED BY: DRAWN BY:

SCALE:

FIG. NO.: SHEET NO.:

REV.

A

COMPONENTS AND MATERIALS SPECIFIED HEREIN WILL ALSO CONFORM TO THE APPLICABLE SECTION OF GOODMAN MSP 824(0) WORKMANSHIP STANDARD FOR FIT, FEEL AND FINISH.

CONFIDENTIAL PROPERTY OF THE GOODMAN MANUFACTURING COMPANY, L.P. NOT TO BE USED, COPIED, OR REPRODUCED IN ANY MANNER WITHOUT THE WRITTEN PERMISSION OF GOODMAN MANUFACTURING COMPANY, L.P. EXCEPT AS AUTHORIZED IN WRITING. MUST BE RETURNED UPON DEMAND, ON COMPLETION OF ORDER, OR OTHER PURPOSE FOR WHICH IT WAS LENT.

SPECIAL CHARACTERISTICS

- ◆ = CRITICAL CHARACTERISTIC
- ⊕ = SIGNIFICANT CHARACTERISTIC
- ⊖ = 6 SIGMA

ACCESSORIES LIST

MODEL	DESCRIPTION	√
ABK-20	Anchor Bracket Kit [◇]	
CHTD18-60	Digital room thermostat with 1-stage cool/1-stage heat	
CHT18-60	Standard room thermostat with 1-stage cool/1-stage heat	
FSK01A	Freeze Protection Kit ¹	
LA-01	Low Ambient Kit	
LSK01A	Liquid Line Solenoid Kit	

[◇] Contains 20 brackets; four brackets needed to anchor unit to pad

¹ Installed on indoor coil