


Job Name:	
Tag#	



<b>Submittal Data Sheet</b>	<b>FFQ18Q2VJU / RX18RMVJU9</b>
1.5-Ton Ceiling Mounted Heat Pump System	



Complete warranty details available from your local dealer or at [www.daikincomfort.com](http://www.daikincomfort.com). To receive the 12-Year Parts Limited Warranty, online registration must be completed within 60 days of installation. Online registration is not required in California or Quebec. *If product is installed in a commercial application, limited warranty period is 5 years.*

### Indoor Specifications

Airflow Rate (cfm)	Cooling		Heating	
	H	M	H	M
	448	378	498	420
	L		L	
	275		307	
Sound (dBA) H / M / L	44 / 40 / 32		44 / 40 / 32	
Dimensions (H x W x D) (in)	10-1/4 x 22-5/8 x 22-5/8			
Weight (Lbs)	39			

### Outdoor Specifications

Compressor	Hermetically Sealed Swing Type			
Refrigerant	R-410A			
Factory Charge (Lbs)	2.49			
Refrigerant Oil	PVE (FVC50K)			
Airflow Rate (cfm)	Cooling		Heating	
	H	2,461	H	2,553
Sound Pressure Level (dBA)	54 / 55			
Dimensions (H x W x D) (in)	28-15/16 x 34-1/4 x 12-5/18			
Weight (Lbs)	97			

### Efficiency

Cooling		Heating	
SEER	19.3	HSPF	10.10
EER	12.5	COP	3.36

### Performance

Cooling (Btu/hr)	
Rated (Min/Max)	17,400 (5,100 / 18,800)
Sensible @ AHRI	12,840
Standard Operating Range	50°F – 115°F
Extended Operating Range*	-4°F – 115°F

Rated Cooling Conditions: Indoor: 80°F DB/67°F WB  
Outdoor: 95°F DB/75°F WB

\*With field settings and wind baffle

Heating (Btu/hr)	
1: @ 47° Rated (Min/Max)	21,600 (5,400 / 21,800)
2: @ 17° Rated	14,200
3: @ 5°	9,610
Operating Range	5°F – 65°F

1: Rated Heating Conditions: Indoor: 70°F DB/60°F WB  
Outdoor: 47°F DB/43°F WB  
2: Rated Heating Conditions: Indoor: 70°F DB/60°F WB  
Outdoor: 17°F DB/15°F WB  
3: Heating Conditions: Indoor: 70°F DB/60°F WB  
Outdoor: 5°F DB/5°F WB

### Electrical

	208/60/1	230/60/1
System MCA	12.8	12.8
System MFA	15	15
Compressor RLA	10.75	10.75
Outdoor fan motor FLA	.38	.38
Outdoor fan motor W	110	110
Indoor fan motor FLA	.28	.28
Indoor fan motor W	50	50

MFA: Max. fuse amps MCA: Min. circuit amps (A) FLA: Full load amps (A)  
RLA: Rated load amps (A) W: Fan motor rated output (W)

### Piping

Liquid (in)	1/4
Gas (in)	1/2
Drain (in)	1-1/32
Max. Interunit Piping Length (ft)	98.4
Max. Interunit Height Difference (ft)	65.625
Chargeless (ft)	32.8
Additional Charge of Refrigerant (oz/ft)	.21

Daikin North America LLC 5151 San Felipe, Suite 500 Houston, TX 77056

(Daikin's products are subject to continuous improvements. Daikin reserves the right to modify product design, specifications and information in this data sheet without notice and without incurring any obligations)


# FFQ18Q2VJU Dimensional Data



• DECORATION PANEL

BYF060C2M1W	FRESH WHITE NO. 5
BYF060C2M1S	DAIKIN SILVER

UNIT: inch(mm)



- NOTE
1. STICKING LOCATION FOR MANUFACTURE'S LABEL
  2. IN CASE OF USING WIRELESS REMOTE CONTROLLER, THIS POSITION WILL BE A SIGNAL RECEIVER
  3. WHEN THE TEMPERATURE AND HUMIDITY IN THE CEILING EXCEED 68° F (30°C) AND RH 80% OR THE FRESH AIR INSULATION THICKNESS 3/8 (10) OR MORE OF GLASSWOOL OR POLYETHYLENE FIBER IS REQUIRED.
  4. THROUGH THE INSTALLATION IS ACCEPTABLE UP TO MAXIMUM OF 23-7/16 (595) SQUARE CEILING OPENING. KEEP THE CLEARANCE OF 3/8 (10) OR LESS BETWEEN THE MAIN UNIT AND THE CEILING OPENING SO THAT THE PANEL OVERLAP ALLOWANCE CAN BE ENSURED.


MODEL	AA	AB
FFQ090Q2VJU	1/4 (6.4)	3/8 (9.5)
FFQ120Q2VJU		
FFQ150Q2VJU		1/2 (12.7)
FFQ180Q2VJU		

3D106039

Daikin North America LLC 5151 San Felipe, Suite 500 Houston, TX 77056

(Daikin's products are subject to continuous improvements. Daikin reserves the right to modify product design, specifications and information in this data sheet without notice and without incurring any obligations)

# RX18RMVJU9 Dimensional Data



Daikin North America LLC 5151 San Felipe, Suite 500 Houston, TX 77056

(Daikin's products are subject to continuous improvements. Daikin reserves the right to modify product design, specifications and information in this data sheet without notice and without incurring any obligations)

# Required & Optional Accessories



## Indoor Unit – One Controller & Decoration Panel are Required

Included	Part Number	Description
	BRC1E73	Wired Navigation Remote Controller
	BRC082A42W	Wireless Remote Controller (White)
	BRC082A42S	Wireless Remote Controller (Silver)
	BYFQ60C2W1S	Low Profile Decoration Panel (Silver) - $1-13/16 \times 24-7/16 \times 24-7/16$
	BYFQ60C2W1W	Low Profile Decoration Panel (White) - $1-13/16 \times 24-7/16 \times 24-7/16$
	BRYQ60A2S	Sensor kit (Silver) Intelligent Eye, Comfort Airflow, and Floor Sensor
	BRYQ60A2W	Sensor kit (White) Intelligent Eye, Comfort Airflow, and Floor Sensor
	BDBHQ44C60	Sealing member of air discharge outlet
	KAFQ441BA60	Long-life filter
	DACA-CP2-1	Maxi Orange Condensate Pump
	DACA-CP3-1	Mini Condensate Pump 5 gph
	AZAI6WSCDKA	DKN Cloud Wi-Fi Adaptor

## Outdoor Unit

Included	Part Number	Description
	DACA-WB-1	Powder-Coated Wall-Mounted Bracket
	KPW063A4	Low Ambient Wind Baffle /Air Adjustment Grille (15 & 18)
	KEH063A4E	Drain Pan Heater
	KKG063A42	Back protection wire net (15 & 18)
	KPS063A41	Snow hood (intake side plate) (15 & 18)
	KPS063A44	Snow hood (intake rear plate) (15 & 18)
	KPS063A47	Snow hood (outlet) (15 & 18)
	KKP937A4	Drain Plug for OD Unit

Daikin North America LLC 5151 San Felipe, Suite 500 Houston, TX 77056

(Daikin's products are subject to continuous improvements. Daikin reserves the right to modify product design, specifications and information in this data sheet without notice and without incurring any obligations)