

Job Name:	
Tag#	



Submittal Data Sheet	FTXS15LVJU
1.25-Ton Wall Mounted Indoor Unit	



Complete warranty details available from your local dealer or at www.daikincomfort.com. To receive the 12-Year Parts Limited Warranty, online registration must be completed within 60 days of installation. Online registration is not required in California or Quebec. *If product is installed in a commercial application, limited warranty period is 5 years.*

Indoor Specifications				
	Cooling		Heating	
	H	M	H	M
Airflow Rate (cfm)	568	477	593	505
	L	SL	L	SL
	385	360	417	371
Sound (dBA) H / M / L / SL	45 / 40 / 35 / 32		43 / 38 / 33 / 30	
Dimensions (H x W x D) (in)	13-3/8 x 41-5/16 x 9-3/4			
Weight (Lbs)	31			
Nominal Capacity (Btu/hr)	15,000			

*See Outdoor Unit for Rated Capacities


Piping	
Liquid (in)	1/4
Gas (in)	1/2
Drain (in)	5/8

Electrical			*208/230V
	Cooling	Heating	
Running Current (Rated) (A)	.31/.29*	.31/.29*	
Power Consumption (Rated) (W)	38/38*	38/38*	

Optional Accessories

Included	Part Number	Description
	BRP072A43	Wireless Interface Adapter (S21 Adapter Included)
	DACA-TS-1	Daikin ENVi Intelligent Thermostat Kit
	BRC944B2-A08	Wired Remote Controller Kit (Includes BRC944B2 & BRCW901A08)
	BRCW901A03	Remote Controller Cable - 10 ft (For BRC944B2)
	BRCW901A08	Remote Controller Cable - 25 ft (For BRC944B2)
	KRP928BB2S	Interface adaptor for DIII-NET
	DACA-CP1-1	Inline Condensate Pump (Fits inside all Daikin wall & floor mount units)
	DACA-CP4-1	External Condensate Pump
	KAF970A46	Air-purifying filter with photocatalytic deodorizing function (without frame)

FTXS15LVJU Dimensional Data



Daikin North America LLC 5151 San Felipe, Suite 500 Houston, TX 77056

(Daikin's products are subject to continuous improvements. Daikin reserves the right to modify product design, specifications and information in this data sheet without notice and without incurring any obligations)