

Multi-Room Ductless systems

Submittal Data: DUCT09HP230V1AD			9,000 BTU/H Ceiling Cassette			
Job Name		Location Date				
Purchaser		Engineer				
ibmitted To		For	Reference	Approval	Construction	
Unit Designation		Schedule	No.			
GENERAL FEATURES						
-Quiet Operation -Multi-Speed Fan						
-Medium Static Pressure Capability					3	
-Slim Line Construction 8" high			the second second		1	
-Internal Condensate Drain Pump		<				
-Return Air From Rear Only					10	
-XK-19 Wired Controllers						
-Wireless Remote Controllers						
-Sentry Condensate Overflow Protection		252				
-Limited 5 yr. Parts Warranty		1000 (000) (6):20 (20) (20) (20) (20)		Errer/Causer & GRICE		
, , , , , , , , , , , , , , , , , , ,			100-100-100 (100-100-100) 2000		Parties Treer Du/Of	
System Ratings			Units Sp	ecification & D	ata	
Cooling*						
Rated Capacity	8,500 BTU/H					
		Wired Contr	roller		XK-19	
Heating*						
Rated Capacity	9,500 BTU/H					
Sound Level (Hi/Lo)**		Condensate	e Drain Lift (Heigh	t)	18-in	
Cooling	37/31 dbA				457-mm	
Heating	37/31 dbA					
		Drain Size (OD)		1.0-in	
Air Flow (min/max)					26-mm	
Indoor Fan	147/265 CFM					
Ext Static Pressure (max/min)	0.040/0.025 inch wg					
Electrical R		Retrige	rant Piping Da	ta		
Fan Motor		Refrigera	nt Type		R410A	
Output Power	80 W	Reingeru	n type		IN TOTA	
FLA	0.35 A	Gas Pino	Size (OD)		3/8-in	
	0.33 A	Gas ripe	512e (OD)		5/0-111	
Power Supply		l iquid Din	e Size (OD)		1/4-in	
Normal Operational Voltage	208/230 V, 1 Phase, 60 Hz				1/4-111	
Voltage Range	187 - 253 V	Connectio	n Method		Flared	
MCA	1.0 A	Connectit				
Interconnecting Cable Wire Size	14-4 AWG					
	14-4 AWG	* Test conditi	ons are based on Al	HRI 210/240		
					50	
		**Sound Level ratings are per AHRI 270 and AHRI 350				
non azone-depleting refrigerant					LISTED	



DUCT09HP230V1AD

