

WIFI  
CAPABLE  
(SELECTED MODELS)

# livo+



Inverter Driven Mini Split  
Heat Pump

High Efficiency  
G10 Inverter Technology  
Quiet Comfort

 **GREE**

[www.greecomfort.com](http://www.greecomfort.com)

# LIVO+



**I Feel**  
Senses temperatures surrounding the remote control to adjust airflow and indoor temperature.



**Hidden Display**



## LIVO+ Series Heat Pump Difference

G10 Inverter Technology  
Multiple Fan Speeds  
Self-Diagnostics  
Low Voltage Start-Up  
Selectable Dry Mode

Intelligent Defrost  
Comfortable Sleep Mode  
Auto Restart  
Vertical Swing Louvers  
Backlight Display

Programmable Timer  
Control Lock  
Blue Fin Condenser Coil  
Automatic Operation  
XK-41 Wired Controller (optional)

Universal WIFI Kit  
Part No. WSBE02  
(sold separately)  
Use Part No. WSBE03 for  
LIVS09HP115V1B only

MODELS		LIVS09HP115V1B	LIVS12HP115V1B	LIVS09HP230V1B	LIVS12HP230V1B	LIVS18HP230V1B	LIVS24HP230V1B	LIVS30HP230V1B*	LIVS36HP230V1B&C*	
System Type		HEAT PUMP								
		SYSTEM PERFORMANCE								
Cooling Capacity (min-max)	Btu/h	9,000 (2,764-10,918)	12,000 (3,753-12,500)	9,000 (3,100-9,600)	12,000 (3,753-12,500)	18,000 (7,165-20,001)	22,000 (8,630-23,200)	28,000 (9,500-30,000)	33,600 (7,400-36,000)	
Heating Capacity (min-max)	Btu/h	9,600 (2,081-12,283)	13,000 (3,412-15,013)	9,500 (3,100-12,000)	13,000 (3,924-14,000)	19,000 (7,336-23,498)	23,000 (8,650-26,000)	28,400 (10,000-33,000)	34,600 (15,000-36,000)	
SEER/EER		16/9.55	16/10.55	16/10.0	16/9.25	16/9.0	16/9.75	16/9.3	16/8.2	
HSPF/COP		9.0/3.3	9.0/3.1	9.0/3.5	9.0/3.1	9.0/2.8	9.0/2.9	8.2/3.0	8.2/2.7	
Energy Star®		No								
Cooling Temperature Range	°F	0 - 115	0 - 115	0 - 115	0 - 115	0 - 115	0 - 115	0 - 109	0 - 109	
Heating Temperature Range	°F	-4 - 75	-4 - 75	-4 - 75	-4 - 75	-4 - 75	-4 - 75	-4 - 75	-4 - 75	
		INDOOR UNIT								
Air flow (min-max)	CFM	171-318	194-400	171-318	194-400	282-471	530-706	412-706	412-736	
Sound Level (min-max)	dB(A)	28-42	29-43	28-43	29-45	35-46	36-48	41-56	41-56	
Dehumidification	pt/hr	1.7	3.0	1.7	3.0	3.8	5.3	6.3	7.4	
Unit Dimension (WxHxD)	in	31.1 x 10.8 x 7.9	33.3 x 11.4 x 8.3	31.1 x 10.8 x 7.9	33.3 x 11.4 x 8.3	38.2 x 11.8 x 8.8	42.4 x 12.8 x 9.7	53.2 x 12.8 x 10.0	53.2 x 12.8 x 10.0	
Package Dimension (WxHxD)	in	34.0 x 13.9 x 10.6	36.1 x 14.3 x 10.9	34.0 x 13.9 x 10.6	36.1 x 14.3 x 10.9	40.9 x 15.0 x 12.0	45.1 x 16.1 x 13.2	56.6 x 16.5 x 13.5	56.6 x 16.5 x 13.5	
Weight (Net/Gross)	lbs	19.8 / 24.3	22.1 / 27.6	19.8 / 24.3	23.2 / 28.7	29.8 / 36.4	37.5 / 45.2	41.9 / 57.3	41.9 / 57.3	
		OUTDOOR UNIT								
Compressor Type		G10 INVERTER DRIVEN ROTARY								
Sound Level	dB(A)	53	53	52	53	56	59	62	65	
Unit Dimension (WxHxD)	in	33.4 x 21.3 x 12.6	33.4 x 21.3 x 12.6	30.6 x 21.3 x 12.6	30.6 x 21.3 x 12.6	39.4 x 31.2 x 16.8	38.0 x 27.6 x 15.3	39.4 x 31.2 x 16.8	39.4 x 31.2 x 16.8	
Package Dimension (WxHxD)	in	34.6 x 22.6 x 14.2	34.6 x 22.8 x 14.2	32.3 x 22.8 x 14.0	33.4 x 22.8 x 14.2	40.4 x 29.0 x 17.9	40.4 x 29.0 x 17.9	42.5 x 33.1 x 19.1	42.5 x 33.1 x 19.1	
Weight (Net/Gross)	lbs	62.8 / 68.4	67.3 / 72.8	66.2 / 71.7	69.5 / 75.0	95.9 / 105.8	110.3 / 120.2	154.4 / 163.2	161.0 / 169.8	
Refrigerant Charge - R410A	oz	24.7	31.8	24.7	30.0	49.4	65.3	84.7	91.7	
Coil Type		Copper / Aluminum with BLUE FIN Coating								
		INSTALLATION								
Line Set Size (Liquid - Gas)	in	1/4 - 3/8	1/4 - 3/8	1/4 - 3/8	1/4 - 3/8	1/4 - 1/2	1/4 - 5/8	1/4 - 5/8	1/4 - 5/8	
Pre-Charge Length	ft	25	25	25	25	25	25	25	25	
Max. Line Run	ft	49	66	49	66	82	82	98	98	
Max. Elevation	ft	33	33	33	33	33	33	33	33	
		ELECTRICAL								
Voltage / Phase / Hertz		115V /1/ 60Hz	115V /1/ 60Hz	208-230V /1/ 60Hz	208-230V /1/ 60Hz	208-230V /1/ 60Hz	208-230V /1/ 60Hz	208-230V /1/ 60Hz	208-230V /1/ 60Hz	
Rated Current Cooling	amps	11.3	13.0	5.8	6.0	11.5	12.0	17.0	20.0	
Rated Current Heating	amps	10.7	13.2	6.0	6.7	11.5	12.2	17.5	20.0	
MCA	amps	17	20	9	9	16	16	20	24	
MOCP	amps	25	30	15	15	25	25	30	40	
Interconnecting Wire		AWG14 / 4	AWG14 / 4	AWG14 / 4	AWG14 / 4	AWG14 / 4	AWG14 / 4	AWG14 / 4	AWG14 / 4	
Limited Warranty		5 Years on Parts								

\* Model can not be upgraded with WIFI.



Specifications are subject to change without notice. Manufacturer reserves the right to discontinue or change at any time, specifications or designs without notice or without incurring obligations.  
©2018. All rights reserved.

Contact No. GREE\_LIVO+\_BROCHURE\_050119



SCAN TO LEARN MORE ABOUT  
GREE PRODUCTS OR VISIT US AT  
GREECOMFORT.COM