

MRCOOL UNIVERSAL PERFORMANCE SPECIFICATIONS

MDU18024	Outdoor Temperature		70°F(21°C)				
	°C	°F	Capacity	Power Input	HSPF		
Heating	-30°C	-22°F	18700	3920	4.77		
	-26°C	-15°F	22000	4000	5.50		
	-21°C	-5°F	24000	4200	5.71		
	-15°C	5°F	24000	3350	7.16		
	-8°C	17°F	24000	2900	8.28		
	0°C	32°F	24000	2300	10.43		
	8°C	47°F	26000	1980	13.13		
	15°C	60°F	28000	2100	13.33		
20°C	68°F	28000	2000	14.00			
Cooling	Outdoor Temperature		70°F(21°C)				
	°C	°F	SHC	Capacity	Power Input	EER	SHC
	-15°C	5°F	13816	20400	1070	19.07	16014
	-10°C	14°F	14080	20400	1120	18.21	16320
	0°C	32°F	14044.8	20400	1180	17.29	16279.2
	5°C	41°F	13992	20400	1270	16.06	16218
	10°C	50°F	13816	20400	1320	15.45	16014
	18°C	65°F	14080	20400	1400	14.57	16320
	24°C	75°F	14044.8	20400	1520	13.42	16279.2
	30°C	85°F	13992	20400	1710	11.93	16218
	35°C	95°F	14080	20400	1850	11.03	16320
	41°C	105°F	13904	20400	2250	9.07	16116
	46°C	115°F	14256	20400	2600	7.85	16524
	54°C	129°F	12425	19000	2900	6.55	13490
MDU18036	Outdoor Temperature		70°F(21°C)				
	°C	°F	Capacity	Power Input	HSPF		
	-30°C	-22°F	18400	4150	4.43		
	-26°C	-15°F	21100	4430	4.76		
	-21°C	-5°F	25200	4630	5.44		
	-15°C	5°F	30000	4800	6.25		
	-8°C	17°F	36000	5450	6.61		
	0°C	32°F	36000	4800	7.50		
8°C	47°F	38000	3600	10.56			
15°C	60°F	38000	3150	12.06			
20°C	68°F	38000	3120	12.18			
Cooling	Outdoor Temperature		70°F(21°C)				
	°C	°F	SHC	Capacity	Power Input	EER	SHC
	-15°C	5°F	16029	30600	2050	14.93	20961
	-10°C	14°F	16380	30600	2120	14.43	21420
	0°C	32°F	16333	30600	2200	13.91	21359
	5°C	41°F	16263	30600	2320	13.19	21267
	10°C	50°F	16380	30600	2400	12.75	21420
	18°C	65°F	16380	30600	2500	12.24	21420
	24°C	75°F	16333	30600	2600	11.77	21359
	30°C	85°F	16263	30600	2800	10.93	21267
	35°C	95°F	16380	30600	3100	9.87	21420
	41°C	105°F	16146	30600	4370	7.00	21114
	46°C	115°F	15230	28050	4080	6.88	19916
54°C	129°F	12780	20000	3000	6.67	14200	
MDU18048	Outdoor Temperature		70°F(21°C)				
	°C	°F	Capacity	Power Input	HSPF		
	-30°C	-22°F	26400	5700	4.63		
	-26°C	-15°F	28500	5900	4.83		
	-21°C	-5°F	34200	6200	5.52		
Heating	-15°C	5°F	43000	6920	6.21		
	-8°C	17°F	48000	6880	6.98		

	0°C	32°F		48000	5800	8.28	
	8°C	47°F		50000	4210	11.88	
	15°C	60°F		52000	4650	11.18	
	20°C	68°F		52000	4500	11.56	
Cooling	Outdoor Temperature		80°F(21°C)				
	°C	°F	SHC	Capacity	Power Input	EER	SHC
	-15°C	5°F	48000	3050	15.74	34320	48000
	-10°C	14°F	48000	3100	15.48	35040	48000
	0°C	32°F	48000	3190	15.05	34464	48000
	5°C	41°F	48000	3280	14.63	34800	48000
	10°C	50°F	48000	3400	14.12	35040	48000
	18°C	65°F	48000	3750	12.80	35040	48000
	24°C	75°F	48000	3850	12.47	34464	48000
	30°C	85°F	48900	4100	11.93	35452.5	48900
	35°C	95°F	48900	4720	10.36	35697	48900
	41°C	105°F	48000	5300	9.06	34080	48000
	46°C	115°F	43500	4860	8.95	32190	43500
54°C	129°F	27000	4350	6.21	19170	27000	
MDU18060	Outdoor Temperature		70°F(21°C)				
	°C	°F		Capacity	Power Input	HSPF	
Heating	-30°C	-22°F		27000	6350	4.25	
	-26°C	-15°F		32000	6700	4.78	
	-21°C	-5°F		37000	7000	5.29	
	-15°C	5°F		44000	7160	6.15	
	-8°C	17°F		49000	7100	6.90	
	0°C	32°F		54000	6600	8.18	
	8°C	47°F		56000	5300	10.57	
	15°C	60°F		60000	5400	11.11	
20°C	68°F		60000	5100	11.76		
Cooling	Outdoor Temperature		80°F(21°C)				
	°C	°F	SHC	Capacity	Power Input	EER	SHC
	-15°C	5°F	54000	3650	14.79	36990	54000
	-10°C	14°F	54000	3720	14.52	37800	54000
	0°C	32°F	54000	3900	13.85	37692	54000
	5°C	41°F	54000	4050	13.33	36990	54000
	10°C	50°F	54000	4120	13.11	36990	54000
	18°C	65°F	54000	4250	12.71	37800	54000
	24°C	75°F	54000	4400	12.27	37692	54000
	30°C	85°F	55000	4650	11.83	38225	55000
	35°C	95°F	55000	5410	10.17	38500	55000
	41°C	105°F	54000	6650	8.12	37260	54000
	46°C	115°F	46000	5700	8.07	32660	46000
54°C	129°F	28000	4450	6.29	19880	28000	